

## MV Station

3.5/5/7MVA

- ✓ Cost-saving Solution
- ✓ High Reliability & Safety
- ✓ Plug-and-play installation
- ✓ Trustworthy Adaptability

GoodWe Medium-voltage Station, a compact step-up power center, is capable of enduring various types of environments. It offers the highest power density in an energy-efficient and safe solution comprised of MV switchgear, transformer, and LV switchgear for power transformation in large-scale solar plants. The pre-assembled and cost-effective solution is integrated into a prefabricated 20ft container, ideal for easy transportation and quick installation. The Plug-and-Play design makes grid connection exceptionally easy and rapid, and the modular architecture allows for simplified maintenance. All contained electrical components are type-tested according to strict safety standards, providing safety for operators.



20ft container for easy transportation



Integrated modular design simplifying maintenance



Type-tested components of reliable quality



Outstanding adaption to extreme environments



\*: The MCCB model of UT needs to be selected separately.

Model	GW3500K-MVS	GW5000K-MVS	GW7000K-MVS
<b>Transformer</b>			
Transformer Type	Oil immersed		
Rated Power (kVA)	3500kVA@40°C	5000kVA@40°C	7000kVA@40°C
Winding Connection	Dy11	Dy11 - y11	Dy11 - y11
LV/MV Voltage (kV) <sup>1</sup>	0.8 / 10 ~ 35		
Maximun Input Current at Nominal Voltage (A)	2526	2 × 1804	2 × 2526
Frequency (Hz)	50 / 60		
Tapping range	±2 × 2.5%		
Peak Efficiency Index	≥99%		
Cooling Type	ONAN (Oil Natural Air Natural)		
Impedance	7% (±10%)	7% (±10%)	8% (±10%)
Oil Type	Mineral oil (PCB free)		
Winding Material	Al / Al		
Insulation Class	A		
<b>MV Switchgear</b>			
Insulation Type	SF6 free / SF6		
Rate Voltage (kV)	12.0 ~ 40.5		
Rate Current (A)	630		
Internal Arcing Fault	IAC AFL 20 kA / 1s Optional:25kA / 1s		
Qty.of Feeder	3 feeders (IBI) <sup>2</sup> / 3 feeders (DCV, Optional: CCV)		
<b>LV Room</b>			
ACB Specification	3200A / 800Vac / 3P, 1pcs	3200A / 800Vac / 3P, 2pcs	3200A / 800Vac / 3P, 2pcs
MCCB Specification	250A / 800Vac / 3P, 14pcs	250A / 800Vac / 3P, 20pcs	250A / 800Vac / 3P, 28pcs
<b>Protection</b>			
AC Input Protection	Circuit breaker		
Transformer Protection	Oil-temperature, oil-level,oil-pressure		
LV Overvoltage Protection	AC Type I + II		
<b>General Data</b>			
Dimensions (W × H × D mm)	6058 × 2896 × 2438		
Approximate Weight (t)	<15	<20	<23
Operating Temperature Range (°C)	-25 ~ +55 (>40°C derating)		
Auxiliary Power Supply	5kVA / 400V (Optional: max. 50kVA)		
Ingress Protection Rating	IP54		
Relative Humidity	0~95 %		
Max. Operating Altitude (m)	1000 (Optional: 2000)		
Anti-corrosion Class	C4H (Optional: C5M)		
Noise Emission (dB)	55		
Communication	Standard: RS485, Ethernet Optional: Optical Fiber		
Compliance	IEC 60076, IEC 62271-200, IEC 62271-202, IEC 61439-1/2, EN50708-1		

\*1: SF6 Free:LV/MV Voltage (kV) is 0.8/10-24kV.

\*2: 3 feeders (IBI) for SF6 free.

\*: Please visit GoodWe website for the latest certificates.